Lovibond® Water Testing

Tintometer® Group

Scuba II

Test equipment for the responsible private swimming pool and whirlpool operator

Part Number: 216100-17

Main pool parameters

Whoever as a private pool owner value accurate measurement results of the important pool parameters, such as Chlorine or pH sets, gets with the Scuba II an ideal test device to the hand. The device works intuitively and measures the most important pool parameters of free chlorine, total chlorine, bromine, pH, alkalinity-m and cyanuric acid.

Waterproof

And if the device falls into the water? No problem - the Scuba II is not only waterproof but also buoyant.

Integrated measuring chamber

Take a sample by immersing the measuring chamber in the instrument.

Fast results

Add a reagent and press "Test" button. The result is available within a few seconds. Or in other words: measuring like the pros.

Industry

Pool Domestic | Pool Services

Application

Pool Water Control

Scuba II

Floatable, waterproof and certainly a useful little helper for the pool: The Scuba II is for private pool owners the ideal companion for the bathing season. Measure the most important parameters and hold the results in your hands immediately.

Convince yourself - here's the Scuba II video

Measuring Range

Test Name	Measuring Range	Chemical Method
Alkalinity-m T	0 - 200 mg/l $CaCO_3$	Acid / Indicator
Bromine T	0.2 - 13 mg/l Br_2	DPD
Chlorine T	0.01 - 6.0 mg/l Cl_2 [a)]	DPD
CyA T	1 - 160 mg/l CyA	Melamine
pH-value T	6.5 - 8.4	Phenol Red

Technical Data

Optics	temperature-compensated LED (λ= 530 nm) and photo-sensor
Operation	Foil keypad
Power Supply	2 AAA batteries
Auto – OFF	Yes
Portability	Portable
Environmental Conditions	temperature: 5 – 40 °C relative humidity: 30 – 90 %, non-condensing
Compliance	CE
Dimensions	70 x 45 x 145 mm
Weight	165 g

Delivery Scope

- Scuba II In plastic box
- 20 DPD No.1 tablet reagents
- 20 Phenol Red Photometer tablet reagents
- 10 DPD No.3 tablet reagents
- 10 CyA-Test tablet reagents
- 10 Alka-M-Photometer tablet reagents
- Instruction manual
- 2 Batteries (AAA)
- Stirring rod

Accessories

Title	Part Number
Battery lid for Scuba II	19801802-3
Rubber seal cap for Scuba II	19802218
Stirring rod, blue, 10 cm	364107

Tintometer GmbH
Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
Fax: +49 (0)231/94510-30
sales@tintometer.de
www.lovibond.com
Germany

The Tintometer Limited
Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
water.sales@tintometer.com
www.lovibond.com
UK

Tintometer AG
Hauptstraße 2
5212 Hausen AG
Tel.: +41 (0)56/4422829
Fax: +41 (0)56/4424121
info@tintometer.ch
www.tintometer.ch
Switzerland

Tintometer China
Room 1001, China Life Tower
16 Chaoyangmenwai Avenue,
Beijing, 100020
Tel.: +86 10 85251111 App. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia
Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer Brazil
Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@tintometer.com.br
www.lovibond.com.br
Brazil

Tintometer Inc.
6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@tintometer.us
www.lovibond.com
USA

Tintometer India Pvt. Ltd.
Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@tintometer.com
www.lovibondwater.in
India

Tintometer Spain
Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain

Technical changes without notice
Printed in Germany
Lovibond® and Tintometer® are Trademarks of the Tintometer Group of Companies